

MISTY DELUX



Latest design of sauna heater-steam generator combination! The 4 L water tank is now located conveniently in the front part of the heater. The steam can be directed to the sauna bathers and the cleaning and servicing of the tank is easy. The water tank can be filled manually or automatically. You can see the current water level from the indicator in front of the heater. In the cup on the water tank you can put sauna essences or herbs to make the sauna enjoyment even more complete. The heater can be used as a normal dry sauna heater or with different combinations of humidity and temperature level which are controlled by the control panel.

- ✦ power range 6 – 9 kW
- ✦ for 5 – 14 m³ saunas
- ✦ materials: cast aluminium top, mantel, body and water tank Cr steel
- ✦ rock compartment 25 kgs
- ✦ cleaning and servicing friendly water tank
- ✦ high temperature limiter also for the water tank
- ✦ stainless steel colour
- ✦ digital control panel

Saunatec

Delux control panel for Misty heaters



The digital Delux model gives you the possibility to control and measure both the temperature and relative humidity in your sauna. You can programme the wished temperature, humidity and bathing time in the control panel and 2 sensors inside the sauna take care of the rest. You can also use s.c. smart sauna function which means that the sauna will be ready for bathing at the set time. This microprocessor controlled panel has LED-display, you can also choose the operation language, change off-set, control the sauna light with dimmer, fan and its speed. The pre-setting time is 12h. You can also memorise you favourite bathing climate with 4 program buttons.

HELO STEAMY V or "KLIMAVITA"



Steamy V or "Klimavita" heater is also a combination heater of a traditional sauna heater and a steam generator unit. The 4 L water tank is located conveniently in the front part of the heater making the cleaning and servicing of the tank easy. The water tank can be filled manually. In the cup on the water tank you can put sauna essences to make the sauna enjoyment even more complete. The heater can be used as a normal dry sauna heater or with a combination of different humidity and temperature level controlled by the OT 2 PLD control panel.

- power range 6 – 9 kW
- for 5 – 14 m³ saunas
- materials: inner and outer body and water tank Cr steel.
- rock compartment 25 kgs
- cleaning and servicing friendly water tank
- high temperature limiter also for the water tank
- stainless steel colour
- digital control panel OT 2 PLD

HELO OT 2 PLD control panel for STEAMY V heaters



OT 2 PLD

The digital OT 2 PLD control panel with LED display enables the sauna bather to select the pre-heating time (max. 24h), the temperature and to adjust the steam function. The maximum sauna bathing time is 6 hours.