

## LCX | 425T

The LCX 425T provides runners and walkers with all of the comfort, security and features they demand while providing an amazingly small footprint, and a surprisingly large running surface.



**CYBEX®**

**CYBEX®**

Excitation

# BIG PERFORMANCE, SMALL SPACE

## LCX | 425T



## Features

### Space Saving

A commercial sized running surface in a compact footprint.

### Ultra Low Maintenance

Virtually maintenance free, with a whisper quiet operation.

### Smooth and Powerful

The 3.0 HP motor with PWM control combines with rugged 2.75" rollers to provide exceptionally smooth operation at all speeds.

### Solid and Sleek

Clean, open front design. Solid steel. Vibration free construction.

### Programs

Quick Start, Manual, Heart Rate Control (with user selectable target heart rate), Speed Interval 1, Speed Interval 2, Cardio, Weight Loss, Hill Interval, Rolling Hills, Hills and Pike's Peak. Programs have 10 levels and control both incline and resistance.

### Graphic Display

Upper display may scan or select between distance, calories, calories/hr, METs, pace, and heart rate. Lower display shows time, incline and speed.

### Heart Rate Monitoring

Includes Contact and Polar® capability (chest strap not included). Multi-color heart shaped LED provides color coded feedback of your heart rate.

### Intelligent Suspension 3

Our IS3 deck suspension system flexes primarily at the point of impact absorbing shock where it occurs unlike the traditional floating decks which indiscriminately give way and cause instability in a runner's stride.

### Engineered for Convenience

At hand convenience with split-level consoles, two water bottle sized holders, magazine rack and tabs and a CD player holder.

## Specifications

Elevation Range	0% to 15%
Speed Range	0.5 mph to 11 mph (0.8 kph to 17.6 kph)
Running Surface	20" x 60" (51 CM x 152 CM)
Safety	Permanently attached lanyard with removable key
Dimensions	32" (81 CM) W x 72" (183 CM) L x 61" (155 CM) H
Max User Weight	350 lbs (159 kg)
Compliance	CE, UL, ASTM, CSA, FCC Class B
Standard Colors	Black shrouds with choice of five standard powder coat colors
Connectivity	Provided by CSAFE (Fitlinxx® certification pending)

### WORLD HEADQUARTERS

10 Trotter Drive + Medway, MA 02053, USA  
t 508.533.4300 + f 508.533.5500 + cybexinternational.com

### CYBEX INTERNATIONAL, UK LTD.

10 North Portway Close + Round Spinney + Northampton, NN3 8RQ, UK  
t 44.1604.490.900 + f 44.1604.490.901

### FINANCING/LEASING INFORMATION

501 Kings Highway East + Suite 301 + Fairfield, CT 06825, USA  
t 774.324.8080 + f 800.890.0437



©Copyright 2005 CYBEX International, Inc. All rights reserved. Polar is a registered trademark of Polar Electro Oy. Specifications subject to change. 10/05 ML-19447 BIOSIG INSTRUMENTS, INC. EMG/ECG heart rate technology US Patent No. 5,337,753 and Canadian Patent No. 2,033,014